

2023

KLR® 650 TRAVELER ABS



| POWER | | Rear Tire | 130/80-17 |
|---------------------------------|--|------------------|---|
| Engine | 4-Stroke, single cylinder, DOHC | Front Brakes | Single 300mm disc with 2-piston calipers, ABS |
| Displacement | 652cc | Rear Brakes | Single 240mm disc with single-piston caliper, ABS |
| Bore x Stroke | 100.0 x 83.0mm | DETAILS | |
| Compression Ratio | 9.8:1 | Frame Type | Tubular, Semi-Double Cradle |
| Maximum Torque | 39.1 lb.-ft. @ 4,500rpm | Rake/Trail | 30.0° / 4.8 in |
| Fuel System | DFI w/40mm Throttle Body | Overall Length | 89.8 in |
| Ignition | CDI | Overall Width | 38.2 in |
| Transmission | 5-speed, return shift with wet multi-disc manual clutch | Overall Height | 57.7/56.3 in (screen hi/lo) |
| Final Drive | Sealed Chain | Ground Clearance | 8.3 in |
| PERFORMANCE | | Seat Height | 34.3 in |
| Front Suspension / Wheel Travel | 41mm telescopic fork/ 7.9 in | Curb Weight | 471.7 lb* |
| Rear Suspension / Wheel Travel | Uni-Trak®, single shock with adjustable rebound damping and adjustable spring preload / 8.0 in | Fuel Capacity | 6.1 gal |
| Front Tire | 90/90-21 | Wheelbase | 60.6 in |
| | | Color Choices | Pearl Solar Yellow |
| | | Warranty | 12 Months |

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit bolivia.kawasaki-la.com for full product details.