KLX®230R S







100/100-18

caliper

caliper

F	N	V	V	F	R
	u	, ,			11

Engine 4-stroke single, SOHC, air-cooled

Displacement 233cc

Bore x Stroke 67.0 x 66.0mm

Compression

Ratio

9.4:1

Fuel System DFI® with 32mm Keihin throttle body

Ignition TCBI Electronic Advance

Transmission 6-speed, return shift with wet multi-disc

manual clutch

Final Drive Chain

DETAILS

Rear Tire

Front Brakes

Rear Brakes

Frame Type High-tensile steel, box-section perimeter

Single 240mm petal disc with a dual-piston

Single 220mm petal disc with single-piston

Rake/Trail 25.7°/4.3 in

Overall Length 80.1 in

Overall Width 33.1 in

Overall Height 46.3 in

Ground 10.8 in Clearance

Seat Height 35.4 in

Curb Weight 262.3 lb.*

Fuel Capacity 1.7 gal

Wheelbase 53.1 in

Color Choices Lime Green

Warranty 6 Month Limited Warranty

PERFORMANCE

Front Suspension / Wheel Travel 37mm telescopic fork/8.7 in

Rear Suspension / Wheel Travel Uni-Trak® linkage system and single shock with adjustable spring preload/8.8 in

Front Tire

80/100-21



