

2023

# KX™ 250



LIME GREEN



## POWER

Engine	4-stroke single, DOHC, liquid-cooled
Displacement	249cc
Bore x Stroke	78.0 x 52.2mm
Compression Ratio	14.1:1
Fuel System	DFI® with 44mm Keihin throttle body and dual injectors
Ignition	Digital CDI
Transmission	5-speed, return shift, with wet multi-disc manual clutch
Final Drive	Chain

## PERFORMANCE

Front Suspension / Wheel Travel	48mm inverted telescopic coil spring fork with 23-way compression damping and 20-way rebound damping/12.4 in
Rear Suspension / Wheel Travel	New Uni-Trak® with dual-range (2.25 turns high speed/21-way low-speed) compression damping, 38-way rebound damping and adjustable preload/12.4 in
Front Tire	80/100-21

Rear Tire	110/90-19
Front Brakes	Single semi-floating 270mm Braking® petal disc with dual-piston caliper
Rear Brakes	Single 250mm Braking® petal disc with single-piston caliper

## DETAILS

Frame Type	Aluminum perimeter
Rake/Trail	28.0° / 4.6 in
Overall Length	86.2 in
Overall Width	32.3 in
Overall Height	50.0 in
Ground Clearance	13.6 in
Seat Height	37.8 in
Curb Weight	227.6 lb without fuel / 237.7 lb*
Fuel Capacity	1.64 gal
Wheelbase	58.5 in
Color Choices	Lime Green
Warranty	Not Available

Scan with camera  
to view videos,  
key features  
and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).  
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.  
Specifications subject to change. Visit [bolivia.kawasaki-la.com](http://bolivia.kawasaki-la.com) for full product details.