





80/100-12

caliper

caliper

P	n	1	V I	ъ.
$\mathbf{P}$		w	w	ĸ

**Engine** 2-stroke single, liquid-cooled

**Displacement** 64cc

Bore x Stroke 45.5 x 41.6mm

Compression

Ratio

8.4:1

Fuel System 24mm Mikuni carburetor

**Ignition** CDI with digital advance

**Transmission** 6-speed, return shift, with wet multi-disc

manual clutch

Final Drive Chain

## DETAILS

**Rear Tire** 

**Front Brakes** 

**Rear Brakes** 

Frame Type High-tensile steel semi-double cradle

Single 180mm disc with single-piston

Single 180mm disc with single-piston

Rake/Trail 27°/2.4 in

Overall Length 62.6 in

Overall Width 29.9 in

Overall Height 37.6 in

Ground Clearance

12.0 in

Seat Height 29.9 in

Curb Weight 132.2 lb\*

Fuel Capacity 1.0 gal

Wheelbase 44.1 in

Color Choices Lime Green

**Warranty** Not Available

## **PERFORMANCE**

Front
Suspension /
Wheel Travel

33mm leading axle telescopic fork with 4way rebound damping/8.3 in

Rear Suspension / Wheel Travel Uni-Trak® single shock system with stepless 3-turns rebound damping and fully adjustable spring preload/9.4 in

Front Tire

60/100-14



