## **MULE**<sup>™</sup> 4000







D	N	N	M		D
	u	N.	М	E	М

4-stroke, 2-cylinder, OHV 90° V Liquid-cooled **Engine** 

617cc Displacement

**Maximum Torque** 34.7 lb-ft @ 2,500 rpm

**Bore x Stroke** 2.99x2.68 in

**Compression Ratio** 10:3:1

**Fuel System** 

**Transmission** 

**Final Drive** 

differential lock

**Engine Braking** No

(max)

DFI® with 34mm Mikuni throttle body

Continuously Variable Transmission (CVT) with (H,N,R)

2WD, shaft. Dual mode rear differential with

**Alternator Output** 23 amp

**Rear Brakes** Drum **Ground Clearance** 7.5 in

**Fuel Capacity** 6.3 gal

**Turning Radius** 11.0 ft

**Cargo Bed** 46.3 x 51.6 x 11.4 in **Dimensions** (LxWxH)

**Cargo Bed Load** 

**Capacity** 

**Payload Capacity** 1,327 lb

**Seating Capacity** 

**Towing Capacity** 1,200 lb

Lighting (2) Halogen headlights (2) tail/brake lights

800 lb

## **CAPABILITY**

MacPherson Strut/3.9 in Front Suspension / **Wheel Travel** 

Rear Suspension /

DeDion Axle/2.8 in

**Wheel Travel Front Tires** 

23x11.00-10

**Rear Tires** 

23x11.00-10

**Steering** 

Rack-and-pinion

**Park Brake Type** 

Independent, Mechanical Drum

**Front Brakes** 

Drum

## **DETAILS**

**Overall Length** 116.7 in

**Overall Width** 62.0 in

**Overall Height** 75.8 in

**Curb Weight** 1,338.4 lb\*

Wheelbase 73.6 in

Instruments Parking brake warning light, coolant temperature

warning light, 12V DC outlet, fuel gauge, hour meter

**Color Choices** Dark Royal Red

Warranty Kawasaki STRONG 3-Year Limited Warranty

Scan with camera to view videos, key features and more.

