MULE™ 4010 4x4









Drum

6.9 in

POWER

Engine 4-stroke, 2-cylinder, OHV, 90° V Liquid-cooled

Displacement 617cc

Maximum Torque 34.7 lb-ft @ 2,500 rpm

Bore x Stroke 2.99x2.68 in

Compression Ratio 10:3:1

Fuel System DFI® with 34mm Mikuni throttle body

Transmission Continuously Variable Transmission (CVT) with

(H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear

differential with differential lock

Engine Braking No

Alternator Output 23 amp

(max)

Fuel Capacity 6.3 gal

Turning Radius 11.2 ft

Cargo Bed 46.3 x 51.6 x 11.4 in

Dimensions (LxWxH) 800 lb

Capacity 800 lb

Rear Brakes

Ground Clearance

1,327 lb

Payload Capacity

Seating Capacity 2

Towing Capacity 1,200 lb

Lighting (2) Halogen headlights (2) tail/brake lights

CAPABILITY

Front Suspension / MacPherson Strut/3.9 in Wheel Travel

Rear Suspension / Wheel Travel

DeDion Axle/2.8 in

Front Tires 23x11.00-10

Rear Tires 23x11.00-10

Steering Electric Power Steering (EPS)

Park Brake Type Independent, Mechanical Drum

Front Brakes Drum

DETAILS

Overall Length 116.7 in
Overall Width 62.0 in
Overall Height 75.8 in

Curb Weight 1,433.3 lb*

Wheelbase 73.6 in

Instruments Parking brake warning light, coolant temperature warning light, 12V DC outlet, fuel gauge, hour meter

Color Choices Timberline Green, Dark Royal Red

Warranty Kawasaki STRONG 3-Year Limited Warranty

Scan with camera to view videos, key features and more

