MULE™ 4010 TRANS4x4® FE







D	n	V	V	E	D
Г	11	N	V	г	π

Engine 4-stroke, 2-cylinder, OHV, 90° V Liquid-cooled

Displacement 617cc

34.7 lb-ft @ 2500 rpm **Maximum Torque**

Bore x Stroke 2.99x2.68 in

Compression Ratio

Fuel System DFI® with 34mm Mikuni throttle body

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking

Alternator Output

(max)

23 amp

CAPABILITY

Front Suspension / MacPherson Strut/3.9 in **Wheel Travel**

Rear Suspension / **Wheel Travel**

DeDion Axle/2.8 in

Front Tires 23x11.00-10

Rear Tires 23x11.00-10

Steering Electric Power Steering (EPS)

Park Brake Type Independent, Mechanical Drum

Front Brakes Drum

Rear Brakes Drum **Ground Clearance**

Fuel Capacity 6.3 gal

7.7 in

Turning Radius 12.8 ft

Cargo Bed 50.4 x 47.6 x 11.2 in (2-person) 30.3 x 47.6 x 11.2 in (4-

Dimensions (LxWxH)

Cargo Bed Load

Capacity

800 lb (2-person) 401 lb (4-person)

Payload Capacity 1,330 lb

Seating Capacity 2-4

Towing Capacity 1,200 lb

Lighting (2) Halogen headlights (2) tail/brake lights

DETAILS

Overall Length 128.5 in

Overall Width 58.5 in

Overall Height 78.1 in

Curb Weight 1,614.1 lb*

Wheelbase 85.2 in

Instruments Parking brake warning light, coolant temperature

warning light, horn, 12V DC outlet, fuel gauge, hour

Additional Features Roof, Horn, Universal Key, High Visibility Orange

Seatbelts

Color Choices Bright White

Kawasaki STRONG 3-Year Limited Warranty Warranty



