## **MULE PRO-FX™ EPS LE**







## **POWER**

Engine 4-stroke, 3-cylinder, DOHC, liquid-cooled, gas

Displacement 812cc

Maximum Torque 48.0 lb-ft @ 3,500 rpm

Bore x Stroke 2.83x2.62 in

Compression Ratio 9.5:1

Fuel System DFI® with 34mm throttle body

75 amp

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking Yes

Alternator Output

(max)

## **CAPABILITY**

Front Suspension / Double wishbone/8.7 in Wheel Travel

Rear Suspension / Double wishbone/8.5 in (L) /8.7 in (R)

Front Tires 26x9.00-12, radial
Rear Tires 26x11.00-12, radial

Steering Electric Power Steering (EPS), Tilt steering

Park Brake Type Independent, Mechanical Disc

Front Brakes Dual Disc, 2 piston caliper

Rear Brakes Dual Disc, 1 piston caliper

Ground Clearance 10.4 in Fuel Capacity 7.9 gal

Turning Radius 16.0 ft

Cargo Bed 54.1 x 53.3 x 11.0 in Dimensions (LxWxH)

Cargo Bed Load 999 lb / 600.0 lb CA Model Capacity

Payload Capacity 1,616.3 lb / 1,263.5 for CA Model

Seating Capacity 3

Towing Capacity 2,000 lb

Lighting (2) Halogen headlights. (2) LED headlights

## **DETAILS**

Overall Length 133.3 in
Overall Width 64.0 in

Overall Height 79.7 in

Curb Weight 1,832.4 lb\*

Wheelbase 92.3 in

Instruments Multi-function display includes digital speedometer, fuel

gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse

and parking indicators, seatbelt reminder lamps

Wheel Type Alloy

Additional Features Roof, Cast Aluminum Wheels

Color Choices Firecracker Red

Warranty Kawasaki STRONG 3-Year Limited Warranty



