## **MULE PRO-FX™ EPS LE**







## **POWER**

**Engine** 4-stroke, 3-cylinder, DOHC, liquid-cooled, gas

Displacement 812cc

**Maximum Torque** 48.0 lb-ft @ 3,500 rpm

**Bore x Stroke** 2.83x2.62 in

**Compression Ratio** 9.5:1

**Fuel System** DFI® with 34mm throttle body

**Transmission** Continuously Variable Transmission (CVT) with (H,L,N,R)

**Final Drive** Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

**Engine Braking** 

**Alternator Output** 75 amp

(max)

**Ground Clearance** 10.4 in

**Fuel Capacity** 7.9 gal

**Turning Radius** 16.0 ft

**Cargo Bed** 

**Dimensions (LxWxH)** 

**Cargo Bed Load** Capacity

**Payload Capacity** 

**Seating Capacity** 

**Towing Capacity** 

Lighting

2,000 lb

54.1 x 53.3 x 11.0 in

999 lb / 600.0 lb CA Model

1,616.3 lb / 1,263.5 for CA Model

(2) Halogen headlights. (2) LED headlights

## CAPABILITY

Front Suspension / **Wheel Travel** 

Double wishbone/8.7 in

Rear Suspension / **Wheel Travel** 

Double wishbone/8.5 in (L) /8.7 in (R)

**Front Tires** 26x9.00-12, radial **Rear Tires** 26x11.00-12, radial

Electric Power Steering (EPS), Tilt steering Steering

**Park Brake Type** Independent, Mechanical Disc

**Front Brakes** Dual Disc, 2 piston caliper

**Rear Brakes** Dual Disc, 1 piston caliper

## **DETAILS**

**Overall Length** 133.3 in

**Overall Width** 64.0 in

**Overall Height** 79.7 in

**Curb Weight** 1,832.4 lb\*

Wheelbase 92.3 in

Instruments Multi-function display includes digital speedometer,

fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt

reminder lamps

**Additional Features** Roof, Cast Aluminum Wheels

**Color Choices** Firecracker Red

Warranty Kawasaki STRONG 3-Year Limited Warranty

Scan with camera to view videos, key features and more.

