MULE PRO-FXT™







POWER

Engine 4-stroke, 3-cylinder, DOHC, liquid-cooled, gas

Displacement 812cc

Maximum Torque 48.0 lb-ft @ 3,500 rpm

Bore x Stroke 2.83x2.62 in

Compression Ratio 9.5:1

Fuel System DFI® with 34mm throttle body

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking

Alternator Output 75 amp

(max)

Ground Clearance

Fuel Capacity

Turning Radius

Cargo Bed

Dimensions (LxWxH)

Cargo Bed Load

Capacity

Payload Capacity

Seating Capacity

DETAILS

Overall Length

Overall Width

Towing Capacity

Lighting

10.2 in

7.9 gal

16.0 ft

42.7 x 53.7 x 11.0 in (3-person) / 22.0 x 53.7 x 11.0 in (6-

999 lb (3-person) / 350 lb (6-person) / 348 lb CA Model

person)

1,616.3 lb / 1,263.5 lb CA Model

3-person (1 row), 6 person (2 row)

2,000 lb**

133.3 in

64.0 in

(2) Halogen headlights.

CAPABILITY

Front Suspension / **Wheel Travel**

Double wishbone/8.7 in

Rear Suspension / **Wheel Travel**

Double wishbone/8.5 in (L) /8.7 in (R)

Front Tires

26x9.00-12, radial

Rear Tires

26x11.00-12, radial

Steering

Rack-and-pinion

Park Brake Type

Independent, Mechanical Disc

Front Brakes

Dual Disc, 2 piston caliper Dual Disc, 1 piston caliper

Rear Brakes

Scan with camera to view videos, key features and more.

Overall Height 77.6 in **Curb Weight** 1,887.5 lb* Wheelbase 92.3 in Instruments Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT warning indicator, neutral, reverse and parking indicators, seatbelt reminder lamps **Color Choices** Warranty Kawasaki STRONG 3-Year Limited Warranty