MULE PRO-MX™ EPS CAMO







POWER

Engine 4-stroke, single cylinder, SOHC, 4-valve liquid-cooled

Displacement 695cc

Maximum Torque 42.7 lb-ft @ 5,000 rpm

Bore x Stroke 102.0 x 85.0 mm

Compression Ratio 10.3:1

Fuel System DFI® with 44mm throttle body

Continuously Variable Transmission (CVT) with centrifugal **Transmission**

clutch, (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft, Dual mode rear differential

with differential lock

Engine Braking Yes

Alternator Output

(max)

35.7 amp

CAPABILITY

Double wishbone/8.6 in Front Suspension / Wheel Travel

Rear Suspension / **Wheel Travel**

Double wishbone/9.1 in

Front Tires 25x10.00-12, radial

Rear Tires 25x10.00-12, radial

Steering Electric Power Steering (EPS), Tilt steering

Park Brake Type Independent, Mechanical Disc

Front Brakes Dual Disc, 2 piston caliper

Dual Disc, 1 piston caliper Rear Brakes

Ground Clearance 10.6 in

Fuel Capacity 9.5 gal

Turning Radius 14.0 ft

Cargo Bed 33.4 x 44.1 x 9.1 in

Dimensions (LxWxH)

Cargo Bed Load 699 lb / 600 lb CA Model

Capacity

Payload Capacity 1,200 lb

Seating Capacity

Towing Capacity 1,500 lb

Lighting (2) Halogen headlights. (2) LED headlights

DETAILS

Overall Length 110.0 in

Overall Width 60.0 in

Overall Height 75.8 in

Curb Weight 1,598.6 lb*

Wheelbase 78.9 in

Instruments

Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, EPS warning indicators, neutral, reverse and parking indicators, differential indicator lamp, seatbelt reminder

lamps

Additional Features

Color Choices TrueTimber® HTC Green

Kawasaki STRONG 3-Year Limited Warranty Warranty

Scan with camera to view videos, key features and more.

