


2023

MULE PRO-MX™ EPS LE



| POWER                           |   | Rear Brakes                  |   |
|---------------------------------|---|------------------------------|---|
| Engine                          | 4-stroke, single cylinder, SOHC, 4-valve liquid-cooled                        | Ground Clearance             | Dual Disc, 1 piston caliper   |
| Displacement                    | 695cc   | Fuel Capacity                | 10.6 in   |
| Maximum Torque                  | 42.7 lb-ft @ 5,000 rpm  | Turning Radius               | 9.5 gal   |
| Bore x Stroke                   | 102.0 x 85.0 mm   | Cargo Bed Dimensions (LxWxH) | 14.0 ft   |
| Compression Ratio               | 10.3:1  | Cargo Bed Load Capacity      | 33.4 x 44.1 x 9.1 in  |
| Fuel System                     | DFI® with 44mm throttle body  | Payload Capacity             | 699 lb / 600 lb CA Model  |
| Transmission                    | Continuously Variable Transmission (CVT) with centrifugal clutch, (H,L,N,R)   | Seating Capacity             | 1,200 lb  |
| Final Drive                     | Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock | Towing Capacity              | 2   |
| Engine Braking                  | Yes   | Lighting                     | 1,500 lb  |
| Alternator Output (max)         | 35.7 amp  |                              | (2) Halogen headlights. (2) LED headlights  |
| CAPABILITY                      |   | DETAILS                      |   |
| Front Suspension / Wheel Travel | Double wishbone/8.6 in  | Overall Length               | 110.0 in  |
| Rear Suspension / Wheel Travel  | Double wishbone/9.1 in  | Overall Width                | 60.0 in   |
| Front Tires                     | 25x10.00-12, radial   | Overall Height               | 75.8 in   |
| Rear Tires                      | 25x10.00-12, radial   | Curb Weight                  | 1,594.2 lb*   |
| Steering                        | Electric Power Steering (EPS), Tilt steering                                  | Wheelbase                    | 78.9 in   |
| Park Brake Type                 | Independent, Mechanical Disc  | Instruments                  | Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, EPS warning indicators, neutral, reverse and parking indicators, differential indicator lamp, seatbelt reminder lamps |
| Front Brakes                    | Dual Disc, 2 piston caliper   | Additional Features          | Roof, Cast Aluminum Wheels  |
|                                 |   | Color Choices                | Super Black   |
|                                 |   | Warranty                     | Kawasaki STRONG 3-Year Limited Warranty   |

Scan with camera to view videos, key features and more.

\*Requires Optional Hitch  
\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).  
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit bolivia.kawasaki-la.com for full product details.