## MULE SX<sup>™</sup> 4x4 FI









## **POWER**

**Engine** 4-stroke, single-cylinder, OHV, air-cooled

Displacement 401cc

**Maximum Torque** 21.4 lb-ft @ 2,400 rpm

**Bore x Stroke** 3.23x2.99 in

**Compression Ratio** 

**Fuel System Fuel Injection** 

**Transmission** Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

**Engine Braking** 

**Alternator Output** 

(max)

22.9 amp

Rear Brakes	Drum
Ground Clearance	6.7 in
Fuel Capacity	4.2 gal
Turning Radius	10.8 ft
Cargo Bed	35.6 x 40.9 x 9.6 in

**Dimensions** (LxWxH)

**Cargo Bed Load** 

399 lb

Capacity

915 lb

**Seating Capacity** 

**Towing Capacity** 

**Payload Capacity** 

1,100 lb\*\*

(2) Halogen headlights, tail/brake lights

## **CAPABILITY**

Front Suspension / MacPherson Strut/3.1 in **Wheel Travel** 

**Rear Suspension /** 

Unit Swingarm/3.1 in

**Wheel Travel Front Tires** 

24x9.00-10

**Rear Tires** 24x11.00-10

Steering Rack-and-pinion

**Park Brake Type** 

Independent, Mechanical Drum

**Front Brakes** Drum

## **DETAILS**

Lighting

Warranty

**Overall Length** 106.7 in **Overall Width** 52.6 in **Overall Height** 70.9 in **Curb Weight** 1,031.9 lb\*

Wheelbase 70.1 in

Instruments

Fuel gauge, hour meter, oil temp light, parking brake

**Color Choices** Timberline Green, Dark Royal Red

Kawasaki STRONG 3-Year Limited Warranty

Scan with camera to view videos, key features and more.

