
MULE SX™ 4x4 XC FI









POWER

Engine 4-stroke, single-cylinder, OHV, air-cooled

Displacement 401cc

Maximum Torque 21.4 lb-ft @ 2,400 rpm

Bore x Stroke 3.23x2.99 in

Compression Ratio

Fuel System Fuel injection

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

Engine Braking

Alternator Output

(max)

with differential lock

22.9 amp

Rear Brakes	Drum
Ground Clearance	8.1 in

Fuel Capacity 4.2 gal

Turning Radius 11.8 ft

Cargo Bed Dimensions (LxWxH)

35.6 x 40.9 x 9.6 in

Cargo Bed Load Capacity

399 lb

900 lb **Payload Capacity Seating Capacity**

Towing Capacity 1,100 lb**

(2) Halogen headlights, tail/brake lights

CAPABILITY

Front Suspension / MacPherson Strut/3.1 in **Wheel Travel**

Rear Suspension / Wheel Travel

Unit Swingarm/3.1 in

Front Tires 26x9.00-12 **Rear Tires** 26x9.00-12

Steering Rack-and-pinion

Park Brake Type Independent, Mechanical Drum

Front Brakes Drum

DETAILS

Lighting

Warrantv

Overall Length 106.7 in **Overall Width** 52.6 in

Overall Height 73.4 in

Curb Weight 1,082.7 lb*

Wheelbase 70.1 in

Instruments Fuel gauge, hour meter, oil temp light, parking brake

Color Choices Timberline Green, Firecracker Red

Kawasaki STRONG 3-Year Limited Warranty

Scan with camera to view videos, key features and more.

