UPDATED 2023 NINJA® 650 KRT EDITION







POWER

Engine	4-stroke, Parallel Twin, DOHC, 8-valve, liquid cooled
Displacement	649cc
Bore x Stroke	83.0 x 60.0mm
Compression Ratio	10.8:1
Fuel System	DFI® with dual 36mm Keihin throttle bodies
Ignition	TCBI with electronic advance
Transmission	6-speed
Final Drive	Sealed chain
Electronic Rider Aids	Kawasaki TRaction Control (KTRC - 2-Modes), ABS

Front Tire	120/70x17
Rear Tire	160/60x17
Front Brakes	Dual 300mm petal-type discs and 2-piston calipers (and ABS)
Rear Brakes	Single 220mm petal-type disc and single- piston caliper (and ABS)

DETAILS

es	Frame Type	Trellis, high-tensile steel
	Rake/Trail	24.0°/3.9 in
	Overall Length	80.9 in
	Overall Width	29.1 in
es),	Overall Height	45.1 in
	Ground Clearance	5.1 in
	Seat Height	31.1 in
	Curb Weight	NON ABS: 419.0 lb / ABS: 423.4 lb*
	Fuel Capacity	4.0 gal
ıg	Wheelbase	55.5 in
	Color Choices	Lime Green/Ebony
	Warranty	12 Month Limited Warranty

PERFORMANCE

Front Suspension / Wheel Travel	41mm hydraulic telescopic fork/4.9 in
Rear Suspension / Wheel Travel	Horizontal back-link with adjustable spring preload/5.1 in

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit bolivia.kawasaki-la.com for full product details.