

2023

NINJA[®] ZX[™] -14R ABS

Kawasaki
Let the Good Times Roll[®]



METALLIC MATTE GRAPHENE STEEL GRAY/FLAT EBONY



POWER

Engine	4-stroke, In-Line Four, DOHC, 16-valve, liquid-cooled
Displacement	1,441cc
Bore x Stroke	84.0 x 65.0mm
Compression Ratio	12.3:1
Fuel System	DFI [®] with 44mm Mikuni throttle bodies (4)
Ignition	TCBI, battery powered & Electronic Advance
Transmission	6-speed, return shift
Final Drive	Sealed chain
Electronic Rider Aids	Kawasaki TRaction Control (KTRC), Power Modes, Anti-lock Brake System (ABS)

Rear Tire	190/50ZR17
Front Brakes	Dual semi-floating 310mm Brembo discs with dual radial-mounted Brembo 4-piston M50 monobloc calipers and ABS
Rear Brakes	Single 250mm disc with twin-piston caliper and ABS

PERFORMANCE

Front Suspension / Wheel Travel	43mm inverted cartridge fork with adjustable preload, 18-way compression and 15-way rebound damping adjustment/4.6 in
Rear Suspension / Wheel Travel	Bottom-link Uni-Trak [®] and gas-charged shock with adjustable preload, stepless rebound and compression damping adjustments, adjustable ride height/4.9 in
Front Tire	120/70ZR17

DETAILS

Frame Type	Aluminum monocoque
Rake/Trail	23.0° / 3.7 in
Overall Length	85.4 in
Overall Width	30.3 in
Overall Height	46.1 in
Ground Clearance	4.9 in
Seat Height	31.5 in
Curb Weight	593.1 lb*
Fuel Capacity	5.8 gal
Wheelbase	58.3 in
Color Choices	Metallic Matte Graphenesteel Gray/Flat Ebony
Warranty	12 Month Limited Warranty

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit bolivia.kawasaki-la.com for full product details.