NINJA® ZX™-6R







METALLIC MATTE GRAPHENESTEEL GRAY/ METALLIC DIABLO BLACK



METALLIC MATTE TWILIGHT BLUE/METALLIC DIABLO BLACK



POWER

Engine 4-stroke, In-Line Four, DOHC, 16-valve, liquid-

cooled

Displacement 636cc

Bore x Stroke 67.0 x 45.1mm

Compression

Ratio

12.9:1

Fuel System DFI® w/38mm Keihin throttle bodies (4) and

oval sub-throttles

Ignition TCBI with digital advance

Transmission 6-speed, return shift

Final Drive Sealed chain

Electronic Rider

Aids

Kawasaki TRaction Control (KTRC), Power Mode, Kawasaki Intelligent anti-lock Brake System (KIBS), Kawasaki Quick Shifter (KQS)

(upshift only)

PERFORMANCE

Front
Suspension /
Wheel Travel

41mm inverted Showa SFF-BP fork with top-out springs, stepless compression and rebound damping, adjustable spring preload/4.7 in

Rear Suspension / Wheel Travel

Bottom-link Uni-Trak® with gas-charged shock, stepless compression damping adjustment, 25-way adjustable rebound damping, fully adjustable spring preload/5.9 in

Front Tire 120/70 ZR17

Rear Tire 180/55 ZR17

Front Brakes Dual 310mm petal discs with dual radial-

mounted, Nissin 4-piston, monobloc calipers

Rear Brakes Single 220mm petal discs with single-piston

caliper

DETAILS

Frame Type Aluminum perimeter

Rake/Trail 23.5°/4.0 in

Overall Length 79.7 in.

Overall Width 28.0 in

Overall Height 43.3 in.

Ground 5.1 in Clearance

Seat Height 32.7 in

Curb Weight 425.6 lb.*

Fuel Capacity 4.5 gal

Wheelbase 55.1 in.

Color Choices Metallic Matte Graphenesteel Gray/Metallic

Diablo Black, Metallic Matte Twilight Blue/

Metallic Diablo Black

Warranty 12 Month Limited Warranty



