## <sup>2023</sup> NINJA<sup>®</sup> ZX<sup>™</sup>-6R KRT EDITION





LIME GREEN/EBONY



## POWER

4-stroke, In-Line Four, DOHC, 16-valve, liquid- cooled
636cc
67.0 x 45.1mm
12.9:1
DFI® w/38mm Keihin throttle bodies (4) and oval sub-throttles
TCBI with digital advance
6-speed, return shift
Sealed chain
Kawasaki TRaction Control (KTRC), Power Mode, Kawasaki Intelligent anti-lock Brake System (KIBS), Kawasaki Quick Shifter (KQS) (upshift only)

## PERFORMANCE

Front	41mm inverted Showa SFF-BP fork with top-out
Suspension /	springs, stepless compression and rebound
Wheel Travel	damping, adjustable spring preload/4.7 in
Rear Suspension / Wheel Travel	Bottom-link Uni-Trak <sup>®</sup> with gas-charged shock, stepless compression damping adjustment, 25- way adjustable rebound damping, fully adjustable spring preload/5.9 in

Front Tire	120/70 ZR17
Rear Tire	180/55 ZR17
Front Brakes	Dual 310mm petal discs with dual radial- mounted, Nissin 4-piston, monobloc calipers (and KIBS ABS)
Rear Brakes	Single 220mm petal discs with single-piston caliper (and KIBS ABS)

## DETAILS

Frame Type	Aluminum perimeter
Rake/Trail	23.5°/4.0 in
Overall Length	79.7 in
Overall Width	28.0 in
Overall Height	43.3 in
Ground Clearance	5.1 in
Seat Height	32.7 in
Curb Weight	NON ABS: 425.6 lb / ABS: 430.0 lb*
Fuel Capacity	4.5 gal
Wheelbase	55.1 in
Color Choices	Lime Green/Ebony
Warranty	12 Month Limited Warranty



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit bolivia.kawasaki-la.com for full product details.