

2023

TERYX KRX[®] 1000 eS

Kawasaki

Let the Good Times Roll[®]



 ICE GRAY/METALLIC ONYX BLACK



POWER		Cargo Bed Dimensions (LxWxH)	
Engine	4-stroke, DOHC, 8-valve parallel-twin, liquid cooled	Cargo Bed Load Capacity	351 lbs
Displacement	999cc	Payload Capacity	781 lbs
Maximum Torque	76.7 lb-ft @ 7000 rpm	Seating Capacity	2
Bore x Stroke	92.0 x 75.1 mm	Towing Capacity	N/A
Compression Ratio	11.5:1	Lighting	(2) LED headlights, (2) LED taillights, LED stoplight
Fuel System	DFI with two 50mm throttle bodies	DETAILS	
Ignition	TCBI with electronic advance	Frame	Ladder type, tubular steel
Starting System	Electric	Overall Length	132.1 in
Transmission	Automatic CVT with centrifugal clutch (H,L,N,R)	Overall Width	68.1 in
Final Drive	Selectable 2WD/4WD with locking front differential, shaft	Overall Height	77.0 in
Engine Braking	Yes	Curb Weight	1944.8 lbs (1947.0 CA)*
CAPABILITY		Wheelbase	98.8 in
Front Suspension / Wheel Travel	Double wishbone, FOX 2.5 Podium Live Valve Internal Bypass shocks with piggyback reservoir, fully adjustable preload, and KECS controlled compression damping/18.6 in.	Instruments	Multi-function digital meter with high-grade full-color TFT LCD screen that offers three selectable display modes (Digital, Analogue, Simple) and can auto adjust screen brightness to suit available light. Display functions include speedometer, tachometer, fuel gauge, gear indicator (L, H, N, R), driving mode (2WD/4WD/4WD+Diff Lock), power mode (Full/Low), suspension mode (Soft/Normal/Firm), clock, CVT temperature, digital tachometer, odometer, dual trip meters, total time, trip time, average speed, water temperature, battery voltage, Bluetooth indicator, telephone call indicator, main indicator, economical riding indicator, maintenance reminder, neutral indicator, reverse indicator, headlight high-beam indicator, battery warning lamp, EPS warning lamp, CVT belt warning lamp, seatbelt warning lamp, parking indicator lamp, oil warning lamp, water temperature warning lamp, engine check lamp.
Rear Suspension / Wheel Travel	4-link trailing-arm rear suspension, FOX 2.5 Podium Live Valve Internal Bypass shocks with piggyback reservoir, fully adjustable preload, and KECS controlled compression damping/21.1 in.	Wheel Type	Alloy with bead-lock wheels
Front Tires	MAXXIS Carnivore 31 x 10.00R15 8PR	Additional Features	Roof, Front Bumper
Rear Tires	MAXXIS Carnivore 31 x 10.00R15 8PR	Color Choices	Ice Gray/Metallic Onyx Black
Steering	Electric Power Steering (EPS) / rack-and-pinion	Warranty	6 Month Limited Warranty
Front Brakes	Dual hydraulic discs with two-piston calipers		
Rear Brakes	Dual hydraulic discs with single-piston calipers		
Ground Clearance	14.4 in (max), 14.0 in (std)		
Standard Ground Clearance/Maximum Ground Clearance†	14.4 in (max), 14.0 in (std)		
Fuel Capacity	10.6 gal		
Turning Radius	20.3 ft		

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The Teryx[®] side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki Teryx side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit bolivia.kawasaki-la.com for full product details.