2023 **TERYX KRX[®]4 1000 eS SPECIAL EDITION**





METALLIC FLAT RAW GRAYSTONE



POWER

CAPABILITY Front Suspension /

Wheel Travel

Wheel Travel

Front Tires

Rear Tires

Steering

Front Brakes

Rear Brakes

Ground Clearance Fuel Capacity

Turning Radius

Rear Suspension /

Engine	4-stroke, DOHC, 8-valve parallel-twin, liquid cooled	
Displacement	999cc	
Maximum Torque	76.7 lb-ft @ 7000 rpm	
Bore x Stroke	92.0 x 75.1 mm	
Compression Ratio	11.5:1	
Fuel System	DFI with two 50mm throttle bodies	
Ignition	TCBI with electronic advance	
Starting System	Electric	
Transmission	Automatic CVT with centrifugal clutch (H,L,N,R)	
Final Drive	Selectable 2WD/4WD with locking front differential, shaft	
Engine Braking	Yes	

Cargo Bed Dimensions (LxWxH)	14.6 x 33.1 x 9.1 in	
Cargo Bed Load Capacity	351 lbs	
Payload Capacity	1001 lbs	
Seating Capacity	4	
Towing Capacity	N/A	
Lighting	ing (2) LED headlights, (2) LED taillights, LED stoplight	

DFTAILS

TCBI with electronic advance			
Electric	Frame	Ladder type, tubular steel	
Automatic CVT with centrifugal clutch (H,L,N,R)	Overall Length	157.3 in	
Selectable 2WD/4WD with locking front differential, shaft	Overall Width	68.1 in	
Yes	Overall Height	79.3 in	
	Curb Weight	2207.2 lbs (2209.4 lbs CA)*	
	Wheelbase	125.8 in	
 Double wishbone, FOX 2.5 Podium Live Valve Internal Bypass shocks with piggyback reservoir, fully adjustable preload, and KECS controlled compression damping/18.6 in. 4-link trailing-arm rear suspension, FOX 2.5 Podium Live Valve Internal Bypass shocks with piggyback reservoir, fully adjustable preload, and KECS controlled compression damping/21.1 in. MAXXIS Carnivore 31 x 10.00R15 8PR Electric Power Steering (EPS) / rack-and-pinion Dual hydraulic discs with two-piston calipers 	Instruments	Multi-function digital meter with high-grade full-color TFT LCD screen that offers three selectable display modes (Digital, Analogue, Simple) and can auto adjust screen brightness to suit available light. Display functions include speedometer, tachometer, fuel gauge, gear indicator (L, H, N, R), driving mode (2WD/4WD/4WD+Diff Lock), power mode (Full/Low), suspension mode (Soft/Normal/Firm), clock, CVT temperature, digital tachometer, odometer, dual trip meters, total time, trip time, average speed, water temperature, battery voltage, Bluetooth indicator**, telephone call indicator, main indicator, economical riding indicator, maintenance reminder, neutral indicator, reverse indicator, headlight high-beam indicator, battery warning lamp, EPS warning lamp, CVT belt warning lamp, seatbelt warning lamp, parking indicator lamp, oil warning lamp, water temperature warning lamp, engine check lamp.	
Dual hydraulic discs with single-piston calipers	Additional Features	Roof, Hifonics® Bluetooth®/AM/FM Audio System, WARN® VRX 45	
14.4 in (max), 13.6 in (std)		Winch	
10.6 gal	Color Choices	Metallic Flat Raw Graystone	
23.3 ft	Warranty	6 months	

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). **When linked to a smartphone via Bluetooth, notification of call and messages received will be indicated on the instrument display. Note, compatibility is limited to iOS type smartphones.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The Teryx® side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki Teryx side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit bolivia.kawasaki-la.com for full product details.