## TERYX KRX®4 1000 SE







LIME GREEN/METALLIC ONYX BLACK



SUNBEAM RED/METALLIC ONYX BLACK



## **POWER**

**Engine** 4-stroke, DOHC, 8-valve parallel-twin, liquid cooled

Displacement 999cc

**Maximum Torque** 76.7 lb-ft @ 7000 rpm

**Bore x Stroke** 92.0 x 75.1 mm

**Compression Ratio** 

**Fuel System** DFI with two 50mm throttle bodies

TCBI with electronic advance Ignition

**Starting System** Electric

Automatic CVT with centrifugal clutch (H,L,N,R) **Transmission** 

**Final Drive** Selectable 2WD/4WD with locking front differential, shaft

**Engine Braking** 

**Turning Radius** 23.3 ft

14.6 x 33.1 x 9.1 in Cargo Bed Dimensions (LxWxH)

**Cargo Bed Load** 

Capacity

351 lbs

**Payload Capacity** 

1001 lbs

**Seating Capacity** 

**Towing Capacity** 

N/A

Lighting

(2) LED headlights, (2) LED taillights, LED stoplight

## **DETAILS**

Ladder type, tubular steel Frame

**Overall Length** 157.3 in **Overall Width** 68.1 in **Overall Height** 79.3 in

2163.1 lbs (2165.3 lbs CA)\* **Curb Weight** 

Wheelbase 125.8 in

Instruments

Multi-function digital meter with bar-style tachometer (2 display options), digital speedometer, bar-style fuel gauge, gear indicator (L, H, N, R), Power Mode, driving mode (2WD/4WD/4WD+Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, bar-style CTV temperature, seatbelt warning lamp, oil warning lamp,

engine check lamp, water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator lamp, EPS warning lamp, and CVT belt warning lamp.

**Additional Features** Roof, WARN® VRX 45 Winch

**Color Choices** Lime Green/Metallic Onyx Black, Sunbeam Red/Metallic Onyx

Black

Warranty 6 months

## **CAPABILITY**

Front Suspension / Wheel Travel

Steering

Double wishbone, FOX 2.5 LSC Piggyback Shocks, dual-rate coil-over springs, fully adjustable preload, and 24-way adjustable compression damping/18.6 in.

Rear Suspension / 4-link trailing-arm rear suspension, FOX 2.5 LSC Piggyback **Wheel Travel** 

Shocks, dual-rate coil-over springs, fully adjustable preload, and 24-way adjustable compression damping/21.1 in.

**Front Tires** MAXXIS Carnivore 31 x 10.00R15 8PR MAXXIS Carnivore 31 x 10.00R15 8PR **Rear Tires** 

Electric Power Steering (EPS) / rack-and-pinion

Dual hydraulic discs with two-piston calipers **Front Brakes** 

**Rear Brakes** Dual hydraulic discs with single-piston calipers

14.4 in (max), 13.6 in (std)

**Fuel Capacity** 10.6 gal

Scan with camera to view videos, key features and more.

**Ground Clearance** 



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The Teryx® side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki Teryx side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2025 Kawasaki Motors Corp., U.S.A.