## TERYX4™









## **POWER**

**Engine** 4-stroke, SOHC, 4-valve V-twin, liquid-cooled

Displacement 783cc

**Maximum Torque** 47.0 lb-ft@ 5500 rpm

**Bore x Stroke** 85.0 x 69.0mm

**Compression Ratio** 10.7:1

**Fuel System** DFI® with two 36mm Mikuni throttle bodies

TCBI with electronic advance Ignition

**Starting System** Electric

**Transmission** Automatic CVT with centrifugal clutch (H,L,N,R)

**Final Drive** Selectable 2WD/4WD with locking front differential,

shaft

**Engine Braking** Yes **Ground Clearance** 11.2 in

**Turning Radius** 16.7 ft

17.9 x 47.6 x 8.7 in **Cargo Bed** 

**Dimensions (LxWxH)** 

**Cargo Bed Load** 249 lb

**Payload Capacity** 

**Fuel Capacity** 

Capacity

1109 lb

7.9 gal

**Seating Capacity** 

**Towing Capacity** 1300 lb

Lighting (2) incandescent headlights, (2) LED taillights, LED

stoplight

## CAPABILITY

Front Suspension / **Wheel Travel** 

Double Wishbone; Fox Podium coil-over shocks with piggyback reservoir, adjustable preload and 24-way

compression damping/8.0 in.

**Rear Suspension / Wheel Travel** 

Double Wishbone; Fox Podium coil-over shocks with piggyback reservoir, adjustable preload and 24-way compression damping/8.3 in.

**Front Tires** Maxxis 26 x 9-12

**Rear Tires** Maxxis 26 x 11-12

**Steering** Electric Power Steering (EPS) / rack-and-pinion

**Front Brakes** Dual hydraulic discs with two-piston calipers

**Rear Brakes** Sealed, oil-bathed, multi-disc

## **DETAILS**

Steel Tube Double-X Reinforcement **Frame** 

**Overall Length** 125.4 in **Overall Width** 60.0 in

**Overall Height** 77.8 in **Curb Weight** 1605.2 lb\*

Wheelbase 85.6 in

Instruments Multi-function digital meter with speedometer, fuel

gauge, clock, hour meter, odometer, dual trip meter and parking-brake indicator, R/N/P/4WD, water temp and

low-oil-pressure indicators

**Wheel Type** Steel

**Color Choices** Metallic Sierra Blue/Metallic Onyx Black

Warranty Kawasaki Strong 3-Year Limited Warranty

Scan with camera to view videos. key features and more.

