





METALLIC MATTE GRAPHENESTEEL GRAY/EBONY



METALLIC SPARK BLACK/METALLIC FLAT SPARK BLACK



POWER

Engine 4-stroke, 2-cylinder, DOHC, liquid-cooled

Displacement 649cc

Bore x Stroke 83.0 x 60.0mm

Compression

Ratio

10.8:1

Maximum

Torque

48.5 lb-ft @ 6,500 rpm

Fuel System

DFI® with Keihin 36mm throttle bodies

Ignition

TCBI with electronic advance

Transmission

6-speed, return shift

Final Drive

Sealed chain

Electronic Rider

Aids

Kawasaki TRaction Control (KTRC - 2 Modes)

PERFORMANCE

Front
Suspension /
Wheel Travel

Telescopic fork/4.9 in

Rear Suspension / Wheel Travel Horizontal back-link with adjustable preload,

swingarm/5.1 in

Front Tire

120/70 ZR17

Rear Tire 160/60 ZR17

Front Brakes Dual 300mm petal-style discs with two-piston calipers (and ABS)

Single 220mm petal-style disc (and ABS)

DETAILS

Rear Brakes

Frame Type Trellis, high tensile steel

Rake/Trail 24.0°/3.9 in

Overall Length 80.9 in

Overall Width 30.1 in

Overall Height 41.9 in

Ground 5.1 in Clearance

Seat Height 31.1 in

Curb Weight NON ABS: 410.1 lb / ABS: 412.3 lb*

Fuel Capacity 4.0 gal

Wheelbase 55.5 in

Special Features Rideology the App Smartphone Connectivity,

TFT Instrumentation

Color Choices Metallic Spark Black/Metallic Flat Spark Black,

Metallic Matte Graphenesteel Gray/Ebony

Warranty 12 Month Limited Warranty



