## 2024 **KLX®140R F**







## **POWER**

			Front Brakes	Sing
	Engine	4-stroke single, SOHC, air-cooled		pist
	Displacement	144cc	Rear Brakes	Sing pist
	Bore x Stroke	58.0 x 54.4mm	DETAILS	
	Compression Ratio			
	Fuel System	20mm Keihin carburetor	Frame Type	Higl
	Ignition	Digital DC-CDI	Rake/Trail	27° ,
	Transmission	5-speed, return shift, with wet multi-disc	<b>Overall Length</b>	78.9
		manual clutch	Overall Width	31.1
	Final Drive	Chain	Overall Height	44.7
PERFORMANCE			Ground	12.4

## INMANUL

Front Suspension / Wheel Travel	33mm telescopic fork/7.5 in	(
Rear Suspension / Wheel Travel	Uni-Trak® linkage system and single shock with piggyback reservoir, 20-way rebound damping and threaded preload adjustability/7.9 in	1
Front Tire	2.75 x 21	1

Rear Tire	4.10 x 18
Front Brakes	Single 220mm petal disc with a dual- piston caliper
Rear Brakes	Single 186mm petal disc with single- piston caliper

	Frame Type	High-tensile steel, box-section perimeter
	Rake/Trail	27°/4.6 in
SC.	<b>Overall Length</b>	78.9 in
	Overall Width	31.1 in
	Overall Height	44.7 in
	Ground Clearance	12.4 in
	Seat Height	33.9 in
	Curb Weight	218.2 lb*
ock	Fuel Capacity	1.5 gal
nd	Wheelbase	52.4 in
	<b>Color Choices</b>	Lime Green, Battle Gray
	Warranty	6 Month Limited Warranty



ÖĈ ۶E

\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit bolivia.kawasaki-la.com for full product details.