KLX®300R









4.6 x 18

piston caliper

piston caliper

Single 270mm petal disc with a dual-

Single 240mm petal disc with single-

POWER

4-stroke single, DOHC, liquid-cooled **Engine**

Displacement 292cc

Bore x Stroke 78.0 x 61.2mm

Compression

Ratio

Fuel System

Ignition TCBI Electronic Advance

11.1:1

Transmission 6-speed, return shift with wet multi-disc

manual clutch

Final Drive Chain

DETAILS

Rear Tire

Front Brakes

Rear Brakes

Semi-Double Cradle **Frame Type**

26.9° / 4.3 in Rake/Trail

Overall Length 86.6 in

Overall Width 32.5 in

Overall Height 49.0 in

Clearance

Ground

Seat Height 35.4 in

Curb Weight 282.2 lb* / 286.7 lb* CA Model

11.8 in

Fuel Capacity 2.1 gal

Wheelbase 56.5 in

Color Choices Lime Green, Battle Gray

6 Month Limited Warranty Warranty

PERFORMANCE

Front Suspension / **Wheel Travel** 43mm inverted telescopic fork with adjustable compression damping /11.2 in

DFI® with 34mm Keihin throttle body

Rear Suspension / **Wheel Travel** Uni-Trak® gas charged shock with piggyback reservoir with adjustable compression, rebound damping and

spring preload/11.2 in

Front Tire 3.0 x 21

Scan with camera to view videos. key features and more.

