2024 **KLX°300SM**







Rear Tire 130/70-17 POWER **Front Brakes** Single 300mm petal disc with a dualpiston caliper 4-stroke single, DOHC, liquid-cooled Engine **Rear Brakes** Single 240mm petal disc with single-Displacement 292cc piston caliper **Bore x Stroke** 78.0 x 61.2mm DETAILS Compression 11.1:1 Ratio Semi Double Cradle Frame Type DFI[®] with 34mm Keihin throttle body **Fuel System** Rake/Trail 25.0°/2.8 in Ignition CDI 83.3 in **Overall Length** Transmission 6-speed, return shift with wet multi-disc manual clutch **Overall Width** 31.1 in **Final Drive** Chain **Overall Height** 44.7 in Ground 9.3 in PERFORMANCE Clearance **Seat Height** 33.9 in 43mm inverted cartridge fork with Front adjustable compression damping / 9.1 in Suspension / **Curb Weight** 304.3 lb* Wheel Travel **Fuel Capacity** 2.0 gal Uni-Trak[®] gas charged shock with Rear piggyback reservoir with adjustable Suspension / Wheelbase 56.5 in Wheel Travel rebound damping and spring preload/ 8.1 in **Color Choices** Battle Gray, Phantom Blue 110/70-17

Front Tire

Scan with camera to view videos. key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit bolivia.kawasaki-la.com for full product details.

Warranty

12 Month Limited Warranty