







D	N	V	V	С	D
r		V	V	r	ĸ

2-stroke single with exhaust power valve (KIPS), liquid-cooled

Displacement 112cc

Bore x Stroke 52.5 x 51.6mm

Compression 9.9:1 (low speed) / 8.6:1 (high speed) **Ratio**

Fuel System 28mm Keihin carburetor

Ignition CDI with Digital Advance

Transmission 6-speed, return shift, with wet multi-disc

manual clutch

Final Drive Chain

Rear Tire	90/100-16
Front Brakes	Single 220mm petal disc with dual-piston caliper
Rear Brakes	Single 184mm petal disc with single-piston caliper

DETAILS

Frame Type	High-tensile steel perimeter design with subframe member	
Rake/Trail	29° /4.3 in	
Overall Length	75.6 in	
Overall Width	30.1 in	
Overall Height	45.3 in	
Ground Clearance	13.0 in	
Seat Height	34.3 in	
Curb Weight	169.7 lb*	
Fuel Capacity	1.32 gal	
Wheelbase	51.6 in	
Color Choices	Lime Green	

Not Available

PERFORMANCE

Front 36mm Suspension / with 2 Wheel Travel

36mm inverted telescopic cartridge fork with 20-way compression damping/10.8 in

Rear Suspension / Wheel Travel Uni-Trak® gas charged shock with piggyback reservoir with 24-way compression and 21-way rebound damping plus adjustable spring preload/10.8 in

Front Tire

70/100-19





Warranty