## **KX**<sup>™</sup>450X







I VIILII	P	0	W	E	R
----------	---	---	---	---	---

**Engine** 4-stroke single, DOHC, liquid-cooled

Displacement 449cc

Bore x Stroke

96.0 x 62.1mm

Compression

Ratio

12.5:1

Fuel System

DFI® with 44mm Keihin throttle body

Ignition

Digital CDI with handlebar-controlled Power

Modes

**Transmission** 

**Final Drive** 

5-speed, return shift, with wet multi-disc manual clutch and hydraulic clutch actuation

Chain

**Electronic Rider** 

Power Modes, Kawasaki TRaction Control (KTRC),

Aids

Launch Control Mode

## **PERFORMANCE**

Front Suspension / Wheel Travel

49mm inverted telescopic coil-spring fork with 21way adjustable compression and 22-way adjustable rebound damping/12.0 in

Rear Suspension / Wheel Travel

Uni-Trak® gas charged shock with piggyback reservoir with adjustable dual-range compression damping (19-way low speed and 4.25 turn stepless high speed), 23-way adjustable rebound damping and stepless adjustable preload/12.1 in

**Front Tire** 80/100-21

**Rear Tire** 120/80-18

Front Brakes Single semi-floating 270mm Braking/Sunstar

petal disc with Brembo master cylinder and dual-

piston caliper

**Rear Brakes** Single 240mm Braking/Sunstar petal disc with

single-piston caliper

## **DETAILS**

Frame Type Aluminum perimeter

Rake/Trail 27.0°/4.6 in

Overall Length 85.6 in

Overall Width 32.1 in

Overall Height 49.6 in

**Ground Clearance** 13.2 in

Seat Height 37.4 in

Curb Weight 239.8 lb\* without fuel / 249.9 lb\*

Fuel Capacity 1.64 gal

Wheelbase 58.3 in

Special Features | Smartphone Connectivity via RIDEOLOGY THE APP

Color Choices Lime Green

Warranty Not Available



