²⁰²⁴ **KX**™65







Rear Tire 80/100-12 POWER Single 180mm disc with single-piston **Front Brakes** caliper Engine 2-stroke single, liquid-cooled **Rear Brakes** Single 180mm disc with single-piston Displacement 64cc caliper **Bore x Stroke** 44.5 x 41.6mm DETAILS Compression 8.4:1 Ratio High-tensile steel semi-double cradle Frame Type 24mm Mikuni carburetor **Fuel System** Rake/Trail 27°/2.4 in Ignition CDI with Digital Advance **Overall Length** 62.6 in 6-speed, return shift, with wet multi-disc Transmission manual clutch **Overall Width** 29.9 in **Final Drive** Chain **Overall Height** 37.6 in Ground 12.0 in PERFORMANCE Clearance **Seat Height** 29.9 in 33mm leading axle telescopic fork with 4-Front Suspension / way rebound damping/8.3 in **Curb Weight** 132.2 lb* Wheel Travel **Fuel Capacity** 1.0 gal Uni-Trak[®] single shock system with Rear stepless 3-turns rebound damping and Suspension / Wheelbase 44.1 in Wheel Travel fully adjustable spring preload/9.4 in **Color Choices** Lime Green **Front Tire** 60/100-14

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit bolivia.kawasaki-la.com for full product details.

Not Available

Warranty