MULE PRO-FX™ 1000 HD EDITION







POWER

Engine 4-stroke, 2-cylinder, DOHC, liquid-cooled, gas

Displacement 999cc

Maximum Torque 61.5 lb-ft

Bore x Stroke 92.0 x 75.1mm

Compression Ratio 10.1:1

Fuel System DFI® with 38mm throttle body

Transmission Continuously Variable Transmission (CVT) with (L,H,N,R)

Final Drive Selectable 2WD/4WD, shaft Dual mode rear differential

with differential lock

Double wishbone/11.0 in

Engine Braking Yes

Alternator Output 90 amp

(max)

Fuel Capacity 7.9 gal

Cargo Bed 54.1 x 53.3 x 11.0 in Dimensions (LxWxH)

Cargo Bed Load Capacity

Turning Radius

capacity

Payload Capacity

Seating Capacity

Towing Capacity

Lighting

999 lb / 600.0 lb CA Model

1,616.3 lb / 1,263.5 lb CA Model

3

2,000 lb

16.0 ft

(2) Halogen headlights. (2) LED headlights

DETAILS

Overall Width

Overall Length 136.6 in

Overall Height 81.1 in

Curb Weight 1,891.9 lb* / 1,894.1 lb* CA Model

64.0 in

Wheelbase 92.3 in

Instruments Multi-function display includes digital speedometer, fuel

gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT warning indicator, neutral, reverse and parking indicators, seatbelt reminder lamps

Wheel Type Steel

Additional Features Roof, Rear Bumper, Additional Under Seat Storage Bin,

Rearview Mirror, Hydraulic Cargo Bed Lift, Self-Leveling

Rear Suspension, Anti-cinch Seatbelts

Color Choices Firecracker Red

Warranty Kawasaki STRONG 3-Year Limited Warranty

CAPABILITY

Front Suspension /

Wheel Travel Rear Suspension / Double wishbone / 10.1 in **Wheel Travel Front Tires** 26 x 9.00-12, radial **Rear Tires** 26 x 11.00-12, radial **Steering** Rack-and-pinion Independent, Mechanical Disc **Park Brake Type Front Brakes** Dual Disc, 2 piston caliper **Rear Brakes** Dual Disc, 1 piston caliper

11.9 in (max), 11.8 in (std)



Ground Clearance

