## **MULE PRO-FXR™ 1000 LE**









## **POWER**

Engine 4-stroke, 2-cylinder, DOHC, liquid-cooled, gas

**Displacement** 999cc

Maximum Torque 61.5 lb-ft

Bore x Stroke 92.0 x 75.1mm

Compression Ratio 10.1:1

Fuel System DFI® with 38mm throttle body

Transmission Continuously Variable Transmission (CVT) with (L,H,N,R)

Final Drive Selectable 2WD/4WD, shaft Dual mode rear differential

with differential lock

Engine Braking Yes

Alternator Output

(max)

90 amp

## **CAPABILITY**

Front Suspension / Double wishbone/11.0 in Wheel Travel

Rear Suspension / Wheel Travel Double wishbone/10.1 in

 Front Tires
 27 x 9.00-12, radial

 Rear Tires
 27 x 11.00-12, radial

Steering Electric Power Steering (EPS), Tilt steering

Park Brake Type Independent, Mechanical Disc

Front Brakes Dual Disc, 2 piston caliper

Rear Brakes Dual Disc, 1 piston caliper

**Ground Clearance** 13.2 in (max), 12.2 in (std)

Fuel Capacity 7.9 gal
Turning Radius 14.0 ft

Cargo Bed 37.6 x 53.3 x 11.0 in

Dimensions (LxWxH)

Cargo Bed Load 999 lb / 600.0 lb CA Model

Cargo Bed Load Capacity

Payload Capacity 1,616.3 lb / 1,263.5 lb CA Model

Seating Capacity 3

Towing Capacity 2,000 lb

Lighting (2) Halogen headlights. (2) LED headlights

## **DETAILS**

Overall Length 122.0 in
Overall Width 64.0 in

Overall Height 78.5 in

Curb Weight 1,746.4 lb\* / 1,748.6 lb\* CA Model

Wheelbase 79.7 in

Instruments Multi-function display includes digital speedometer, fuel

gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse

and parking indicators, seatbelt reminder lamps

Additional Features Roof, Rear Bumper, Contoured Two-Tone Bench Seat,
Additional Cup Holders

Color Choices Ice Gray

Warranty Kawasaki STRONG 3-Year Limited Warranty



