## **MULE PRO-MX™ EPS**









## **POWER**

Engine 4-stroke, single cylinder, SOHC, 4-valve liquid-cooled

Displacement 695cc

Maximum Torque 42.7 lb-ft @ 5,000 rpm

Bore x Stroke 102.0 x 85.0mm

Compression Ratio 10.3:1

Fuel System DFI® with 44mm throttle body

Transmission Continuously Variable Transmission (CVT) with

centrifugal clutch, (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft Dual mode rear differential

with differential lock

Engine Braking Yes

Alternator Output 35.7 amp

(max)

Rear Brakes Dual Disc, 1 piston caliper

**Ground Clearance** 10.6 in

Fuel Capacity 9.5 gal

Turning Radius 14.0 ft

Cargo Bed

Dimensions (LxWxH)

699 lb / 600 lb CA Model

33.4 x 44.1 x 9.1 in

Cargo Bed Load Capacity

**Payload Capacity** 

capacity

1,200 lb

Seating Capacity 2

eating capacity

Towing Capacity 1,500 lb

Lighting (2) Halogen headlights. (2) LED headlights

## **CAPABILITY**

Front Suspension / Double wishbone / 8.6 in Wheel Travel

Rear Suspension / Wheel Travel

Double wishbone/9.1 in

Front Tires 25 x

25 x 8.00-12, radial

**Rear Tires** 25 x 10.00-12, radial

Steering Electric Power Steering (EPS), Tilt steering

Park Brake Type

Independent, Mechanical Disc

Front Brakes Dual Disc, 2 piston caliper

## **DETAILS**

Overall Length 110.0 in

Overall Width 60.0 in

Overall Height 74.4 in

Curb Weight 1,587.6 lb\* / 1,589.8 lb\* CA Model

Wheelbase 78.9 in

**Instruments** Multi-function display includes digital speedometer,

fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, EPS warning indicators, neutral, reverse and parking indicators, differential indicator lamp, seatbelt

reminder lamps

Color Choices Timberline Green, Firecracker Red

Warranty Kawasaki STRONG 3-Year Limited Warranty

Scan with camera to view videos, key features and more.

