

UPDATED 2024

MULE PRO-MX™ SE



POWER		Ground Clearance	
Engine	4-stroke, single cylinder, SOHC, 4-valve liquid-cooled	Fuel Capacity	10.6 in
Displacement	695cc	Turning Radius	9.5 gal
Maximum Torque	42.7 lb-ft @ 5,000 rpm	Cargo Bed Dimensions (LxWxH)	14.0 ft
Bore x Stroke	102.0 x 85.0mm	Cargo Bed Load Capacity	33.4 x 44.1 x 9.1 in
Compression Ratio	10.3:1	Payload Capacity	699 lb / 600 lb CA Model
Fuel System	DFI® with 44mm throttle body	Seating Capacity	1,200 lb
Transmission	Continuously Variable Transmission (CVT) with centrifugal clutch, (H,L,N,R)	Towing Capacity	2
Final Drive	Selectable 2WD/4WD, shaft Dual mode rear differential with differential lock	Lighting	1,500 lb
Engine Braking	Yes	DETAILS	
Alternator Output (max)	35.7 amp		
CAPABILITY		Overall Length	111.4 in
Front Suspension / Wheel Travel	Double wishbone/8.6 in	Overall Width	60.0 in
Rear Suspension / Wheel Travel	Double wishbone/9.1 in	Overall Height	75.8 in
Front Tires	25 x 10.00-12, radial	Curb Weight	1,622.9 lb* / 1,625.1 lb* CA Model
Rear Tires	25 x 10.00-12, radial	Wheelbase	78.9 in
Steering	Electric Power Steering (EPS), Tilt steering	Instruments	Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, EPS warning indicators, neutral, reverse and parking indicators, differential indicator lamp, seatbelt reminder lamps
Park Brake Type	Independent, Mechanical Disc	Additional Features	Roof, WARN® VRX 35 Winch, Cast Aluminum Wheels, Painted Body Panels
Front Brakes	Dual Disc, 2 piston caliper	Color Choices	Galaxy Silver
Rear Brakes	Dual Disc, 1 piston caliper	Warranty	Kawasaki STRONG 3-Year Limited Warranty