UPDATED 2024

NINJA® ZX™-10RR ABS







POWER

Engine 4-stroke, In-Line Four, DOHC, 16-valve, liquid-cooled

Displacement 998cc

Bore x Stroke 76.0 x 55.0mm

Compression Ratio 13.0:1

DFI®, 47mm throttle bodies and Variable Air Intake **Fuel System**

System (VAI)

TCBI with Digital Advance Ignition

Transmission 6-speed, return shift

Final Drive Sealed chain

Electronic Rider

Öhlins Electronic Steering Damper, Kawasaki Launch Control Mode (KLCM), Kawasaki Intelligent anti-lock Brake System (KIBS), Sport-Kawasaki TRaction Control (S-KTRC), Kawasaki Engine Braking Control, Kawasaki Quick Shifter (KQS) (upshift & downshift), Kawasaki

(Full/Mid/Low)

PERFORMANCE

Front Suspension / **Wheel Travel**

43mm inverted Balance Free Fork, adjustable stepless rebound and compression damping, spring preload adjustability/4.7 in

Corner Management Function (KCMF), Power Modes

Rear Suspension / Wheel Travel

Horizontal back-link with Balance Free gas-charged shock, stepless, dual-range (low-/high-speed) compression damping, stepless rebound damping, fully

adjustable spring preload/4.5 in

Front Tire 120/70 ZR17

Rear Tire 190/55 ZR17

Brembo dual semi-floating 330mm discs with dual radial **Front Brakes**

mounted monobloc 4-piston calipers, Kawasaki Intelligent anti-lock Brake System (KIBS)

Rear Brakes Single 220mm disc with aluminum single-piston caliper,

Kawasaki Intelligent anti-lock Brake System (KIBS)

DETAILS

Aluminum perimeter **Frame Type** 25.0°/4.1 in Rake/Trail

46.7 in

5.3 in

Overall Length 82.1 in

Overall Width 29.5 in

Overall Height

Ground Clearance

Seat Height 32.9 in

456.4 lb* **Curb Weight**

Fuel Capacity 4.5 gal

Wheelbase 57.1 in

Special Features 4.3" Full-Color TFT Instrumentation, Smartphone

Connectivity via RIDEOLOGY THE APP

Color Choices Lime Green/Ebony

12 Month Limited Warranty Warranty



