## TERYX4™ S CAMO







## **POWER**

**Engine** 4-stroke, SOHC, 4-valve V-twin, liquid-cooled

Displacement 783cc

**Maximum Torque** 47.0 lb-ft @ 5,500 rpm

**Bore x Stroke** 85.0 x 69.0mm

**Compression Ratio** 10.7:1

**Fuel System** DFI® with two 36mm Mikuni throttle bodies

TCBI with Electronic Advance Ignition

**Starting System Flectric** 

**Transmission** Automatic CVT with centrifugal clutch (H,L,N,R)

**Final Drive** Selectable 2WD/4WD with locking front differential,

shaft

**Engine Braking** Yes **Ground Clearance** 12.2 in (max) / 11.2 in (std)

**Fuel Capacity** 7.9 gal

**Turning Radius** 17.7 ft

**Cargo Bed** 17.9 x 47.6 x 8.7 in **Dimensions** 

(LxWxH)

**Cargo Bed Load** 249 lb

Capacity

**Payload Capacity** 1,000 lb

**Seating Capacity** 

**Towing Capacity** 1,300 lb

Lighting (4) LED headlights, (2) LED taillights, LED stoplight

## CAPABILITY

**Wheel Travel** 

Front Suspension / Double wishbone, FOX 2.0 LSC Piggyback Shocks, fully **Wheel Travel** adjustable preload, and adjustable compression

damping/10.7 in

**Rear Suspension /** Double wishbone, FOX 2.0 LSC Piggyback Shocks, fully adjustable preload, and adjustable compression

damping/10.0 in

**Front Tires** Maxxis® 27 x 9-14

**Rear Tires** Maxxis® 27 x 11-14

Steering Electric Power Steering (EPS) / rack-and-pinion

**Front Brakes** Dual hydraulic discs with two-piston calipers

**Rear Brakes** Sealed, oil-bathed, multi-disc

## **DETAILS**

Steel Tube Double-X Reinforcement Frame

**Overall Length** 125.4 in

**Overall Width** 62.6 in **Overall Height** 80.5 in

**Curb Weight** 1,638.3 lb\* / 1,640.5 lb\* CA Model

Wheelbase 88.2 in

Instruments Multi-function digital meter with speedometer, fuel

> gauge, clock, hour meter, odometer, dual trip meter and parking-brake indicator, R/N/P/4WD, water temp

and low-oil-pressure indicators

**Additional Features** Roof

TRUETIMBER® STRATA **Color Choices** 

Warranty Kawasaki Strong 3-Year Limited Warranty

Scan with camera to view videos. key features and more.

