## **MULE PRO-DXT™ FE EPS**









42.7 x 53.7 x 11.0 in (3-person) / 22.0 x 53.7 x 11.0 in (6-

Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters,

reverse and parking indicators, seatbelt reminder lamps

2WD/4WD indicator, water temperature warning

Roof, Horn, Universal Key, High Visibility Orange

indicator, oil pressure warning indicator, glow plug indicator, CVT and EPS warning indicators, neutral,

999 lb (3-person) / 350 lb (6-person)

## **POWER**

Engine 4-stroke, 3-cylinder, OHV, liquid-cooled, diesel

Displacement 993cc

Maximum Torque 38.3 lb-ft @ 2,400 rpm

Bore x Stroke 74.0 x 77.0mm

Compression Ratio 23.5:1

Fuel System Bosch in-line injection pump

Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking Yes

Alternator Output 55 amp

(max)

Payload Capacity
Seating Capacity

**DETAILS** 

**Overall Length** 

**Overall Width** 

**Overall Height** 

**Curb Weight** 

Wheelbase

Instruments

**Cargo Bed Load** 

**Ground Clearance** 

**Fuel Capacity** 

**Turning Radius** 

**Dimensions (LxWxH)** 

Cargo Bed

Capacity

eating Capacity 3-person (1-row), 6-person (2-row)

Towing Capacity 2,0

2,000 lb

133.3 in

64.0 in

79.5 in

92.3 in

1,971.3 lb\*

Seatbelts

1,574 lb

10.2 in

7.9 gal

16.0 ft

person)

Lighting (2) Halogen headlights

## **CAPABILITY**

**Wheel Travel** 

Front Suspension / Double wishbone / 8.7 in Wheel Travel

Rear Suspension / Double wishbone/8.5 in (L)/8.7 in (R)

 Front Tires
 26 x 9-12

 Rear Tires
 26 x 11-12

Steering Electric Power Steering (EPS), Tilt steering

Park Brake Type Independent, mechanical disc

Front Brakes Dual disc, 2-piston caliper

Rear Brakes Dual disc, 1-piston caliper

n caliper Color Choices

Color Choices Bright White

Warranty Kawasaki STRONG 3-Year Limited Warranty

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.

**Additional Features**