

2025

MULE PRO-FX™ 1000 HD EDITION

Kawasaki

Let the Good Times Roll®





FIRECRACKER RED

POWER			
Engine	4-stroke, 2-cylinder, DOHC, liquid-cooled, gas	Ground Clearance	11.9 in (max), 11.8 in (std)
Displacement	999cc	Fuel Capacity	7.9 gal
Maximum Torque	61.5 lb-ft @ 4,500 rpm	Turning Radius	16.0 ft
Bore x Stroke	92.0 x 75.1mm	Cargo Bed Dimensions (LxWxH)	54.1 x 53.3 x 11.0 in
Compression Ratio	10.1:1	Cargo Bed Load Capacity	999/600 lb CA Model
Fuel System	DFI® with 38mm throttle body	Payload Capacity	1,616.3/1,263.5 lb CA Model
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)	Seating Capacity	3
Final Drive	Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock	Towing Capacity	2,000 lb
Engine Braking	Yes	Lighting	(2) Halogen headlights, (2) LED headlights
Alternator Output (max)	90 amp		
CAPABILITY		DETAILS	
Front Suspension / Wheel Travel	Double wishbone/11.0 in	Overall Length	136.6 in
Rear Suspension / Wheel Travel	Double wishbone/10.1 in	Overall Width	64.0 in
Front Tires	26 x 9-12, radial	Overall Height	81.1 in
Rear Tires	26 x 11-12, radial	Estimated Dry Weight	1,816.9/1,819.1 lb** CA Model
Wheel Type	Steel	Curb Weight	1,891.9/1,894.1 lb* CA Model
Steering	Rack-and-pinion	Wheelbase	92.3 in
Park Brake Type	Independent, mechanical disc	Instruments	Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT warning indicator, neutral, reverse and parking indicators, seatbelt reminder lamps
Front Brakes	Dual disc, 2-piston caliper	Additional Features	Roof, Rear Bumper, Additional Under Seat Storage Bin, Rearview Mirror, Hydraulic Cargo Bed Lift, Self-Leveling Rear Suspension, Anti-cinch Seatbelts
Rear Brakes	Dual disc, 1-piston caliper	Color Choices	Firecracker Red
		Warranty	Kawasaki STRONG 3-Year Limited Warranty