


UPDATED 2025

MULE PRO-FX™ 820 EPS

Kawasaki
Let the Good Times Roll®



 **TIMBERLINE GREEN**



POWER

Engine	4-stroke, 3-cylinder, DOHC, liquid-cooled, gas
Displacement	812cc
Maximum Torque	48.0 lb-ft @ 3,500 rpm
Bore x Stroke	72.0 x 66.5mm
Compression Ratio	9.5:1
Fuel System	DFI® with 34mm throttle body
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)
Final Drive	Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock
Engine Braking	Yes
Alternator Output (max)	75 amp

Rear Brakes	Dual disc, 1-piston caliper
Ground Clearance	10.4 in
Fuel Capacity	7.9 gal
Turning Radius	16.0 ft
Cargo Bed Dimensions (LxWxH)	54.1 x 53.3 x 11.0 in
Cargo Bed Load Capacity	999/600 lb CA Model
Payload Capacity	1,616.3/1,263.5 lb CA Model
Seating Capacity	3
Towing Capacity	2,000 lb
Lighting	(2) Halogen headlights

CAPABILITY

Front Suspension / Wheel Travel	Double wishbone/8.7 in
Rear Suspension / Wheel Travel	Double wishbone/8.5 in (L)/8.7 in (R)
Front Tires	26 x 9-12, radial
Rear Tires	26 x 11-12, radial
Wheel Type	Alloy
Steering	Rack-and-pinion w/ Electric Power Steering (EPS), Tilt steering
Park Brake Type	Independent, mechanical disc
Front Brakes	Dual disc, 2-piston caliper

DETAILS

Overall Length	133.3 in
Overall Width	64.0 in
Overall Height	77.4 in
Estimated Dry Weight	1,757.4/1,759.6 lb** CA Model
Curb Weight	1,830.2/1,832.4 lb* CA Model
Wheelbase	92.3 in
Instruments	Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT warning indicator, neutral, reverse and parking indicators, seatbelt reminder lamps
Color Choices	Timberline Green
Warranty	Kawasaki STRONG 3-Year Limited Warranty

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
 **Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
 All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.
 KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2026 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit bolivia.kawasaki-la.com for full product details.