

2025

NINJA[®] ZX[™]-10R KRT EDITION

Kawasaki

Let the Good Times Roll[®]



POWER		Rear Suspension / Wheel Travel	
Engine	4-stroke, in-line 4-cylinder, DOHC, 16-valve, liquid-cooled	Horizontal back-link with Showa Balance Free Rear Cushion (BFRC) lite shock, stepless, dual-range (low-/high-speed) compression damping, stepless rebound damping, fully adjustable spring preload/4.5 in	
Displacement	998cc	Front Tire	120/70 ZR17
Bore x Stroke	76.0 x 55.0mm	Rear Tire	190/55 ZR17
Compression Ratio	13.0:1	Front Brakes	Brembo dual semi-floating 330mm discs with dual radial mounted monobloc 4-piston calipers, Kawasaki Intelligent anti-lock Brake System (KIBS) (ABS only)
Maximum Horsepower	196.0 hp ¹ @ 11,500 rpm	Rear Brakes	Single 220mm disc with aluminum single-piston caliper, Kawasaki Intelligent anti-lock Brake System (KIBS) (ABS only)
Maximum Torque	83.9 lb-ft @ 11,300 rpm	DETAILS	
Fuel System	DFI [®] , 47mm throttle bodies	Frame Type	Aluminum perimeter
Ignition	TCBI with electronic advance	Rake/Trail	25.0° / 4.1 in
Transmission	6-speed	Overall Length	82.1 in
Final Drive	Sealed chain	Overall Width	29.5 in
Electronic Rider Aids	Öhlins Electronic Steering Damper, Electronic Cruise Control, Kawasaki Launch Control Mode (KLCM), Kawasaki Intelligent anti-lock Brake System (KIBS) (ABS only), Sport-Kawasaki TRaction Control (S-KTRC), Kawasaki Engine Braking Control, Kawasaki Quick Shifter (KQS) (upshift & downshift), Kawasaki Corner Management Function (KCMF)	Overall Height	46.7 in
PERFORMANCE		Ground Clearance	5.3 in
Front Suspension / Wheel Travel	43mm inverted Showa Balance Free Fork (BFF), adjustable stepless rebound and compression damping, spring preload adjustability/4.7 in	Seat Height	32.9 in
		Curb Weight	456.4 lb* (ABS), 452.0 lb* (non-ABS)
		Fuel Capacity	4.5 gal
		Wheelbase	57.1 in
		Special Features	4.3" Full-Color TFT Instrumentation, Smartphone Connectivity via RIDELOGY THE APP
		Color Choices	Lime Green/Ebony/Pearl Blizzard White
		Warranty	12 Month Limited Warranty



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2026 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visit bolivia.kawasaki-la.com for full product details.