

2025

RIDGE® XR CREW HVAC

Kawasaki

Let the Good Times Roll®



- ICE GRAY
- METALLIC GRAYSTONE



POWER		DETAILS	
Engine	4-stroke, DOHC, 4-valve, in-line 4-cylinder, liquid-cooled	Fuel Capacity	12.9 gal
Displacement	999cc	Turning Radius	19.0 ft
Maximum Horsepower	116.0 hp ¹ @ 8,500 rpm	Cargo Bed Dimensions (LxWxH)	34.6 x 49.0 x 12.8 in
Maximum Torque	73.8 lb-ft @ 8,000 rpm	Cargo Bed Load Capacity	1,000/600 lb CA Model
Bore x Stroke	73.4 x 59.0mm	Payload Capacity	1,290/1,076 lb CA Model
Compression Ratio	10.6:1	Seating Capacity	4-person (2 row), bucket seats
Fuel System	EFI	Towing Capacity	2,500 lb
Ignition	TCBI with Digital Advance	Lighting	All-LED lighting
Starting System	Electric	Instruments	
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)		
Final Drive	Selectable 4WD with locking front/rear differential, shaft	Frame	Ladder type, tubular steel
Engine Braking	Yes	Overall Length	156.7 in
Alternator Output (max)	85 amp	Overall Width	64.0 in
Electronic Rider Aids	Power Modes, Economical Riding Indicator	Overall Height	82.7 in
CAPABILITY		Estimated Dry Weight	2,403.5/2,405.7 lb** CA Model
		Curb Weight	2,513.7/2,515.9 lb* CA Model
Front Suspension / Wheel Travel	Long-Travel, Double Wishbone/12.7 in	Wheelbase	122.2 in
Rear Suspension / Wheel Travel	Long-Travel, Double Wishbone/12.7 in	Additional Features	
Front Tires	SUNF 30 x 10-14		
Rear Tires	SUNF 30 x 10-14	Color Choices	
Wheel Type	14" Aluminum		
Steering	Rack-and-pinion w/ Electric Power Steering (EPS)	Warranty	
Front Brakes	Dual hydraulic 249mm discs with two-piston calipers		
Rear Brakes	Dual hydraulic 249mm discs with single-piston calipers	Warranty	
Ground Clearance	14.4/15.2 in (max preload); 14.4 in CA Model		

Scan with camera to view videos, key features and more.

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

Specifications subject to change. Visit bolivia.kawasaki-la.com for full product details.