

2026

BRUTE FORCE® 750 SE EPS CAMO

Kawasaki

Let the Good Times Roll®

TRUETIMBER® STRATA

POWER		Fuel Capacity	
Engine	4-stroke, V-twin, SOHC, liquid-cooled	Steering	Rack-and-pinion w/ Electric Power Steering (EPS)
Displacement	749cc	Turning Radius	10.5 ft
Bore x Stroke	85.0 x 66.0mm	Towing Capacity	1,250 lb
Compression Ratio	9.3:1	Total Rack Capacity	264.5 lb
Maximum Horsepower	50.0 hp ¹ @ 6,750 rpm	Rack Capacity, Front/Rear	88.0/176.0 lb
Maximum Torque	42.7 lb-ft @ 4,750 rpm	Lighting	All-LED lighting
Fuel System	DFI® with two 34mm throttle bodies	DETAILS	
Ignition	Digital DC-CDI		
Transmission	Automatic Continuously Variable Transmission (CVT) with (H,L,N,R)	Frame Type	Double-cradle, high-tensile tubular steel
Final Drive	Selectable 2WD/4WD with variable control front differential lock, shaft	Tread Width	37.0/35.6 in
CAPABILITY		Overall Length	86.0 in
Front Suspension / Wheel Travel	Double wishbone, adjustable spring preload/6.9 in	Overall Width	46.1 in
Rear Suspension / Wheel Travel	Double wishbone, adjustable spring preload/7.4 in	Overall Height	47.6 in
Front Tires	AT 25 x 8-12	Seat Height	35.2 in
Rear Tires	AT 25 x 10-12	Estimated Dry Weight	685.8 lb**
Front Brakes	Dual hydraulic 176mm discs with 2-piston calipers	Curb Weight	732.1 lb*
Rear Brakes	Sealed, oil-bathed, multi-disc with independent park brake	Wheelbase	50.6 in
Ground Clearance	9.0 in/9.7 in (max preload)	Instruments	Digital speedometer, 2WD/4WD drive indicator, fuel gauge, odometer, dual trip meters, dual hour meter, clock (12h/24h), battery voltage, Kawasaki service reminder, oil change reminder, high beam, neutral, reverse, and warning lights (engine, coolant temperature, CVT, oil, EPS, and battery voltage)
Starting System	Electric	Special Features	Full-color TFT Instrumentation w/ Smartphone Connectivity via RIDELOGY THE APP POWERSPORTS, QQR™ system
		Color Choices	TRUETIMBER® STRATA
		Warranty	12 Month Limited Warranty

Scan with camera to view videos, key features and more.

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: ATVs can be hazardous to operate. For your safety: Always wear a helmet, eye protection, and protective clothing. Never carry a passenger. Never ride under the influence of drugs or alcohol. Never ride on public roads or pavement. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Kawasaki ATVs with engines over 90cc are intended for use only by persons 16 years of age or older. Kawasaki also recommends that all ATV riders take a training course. For more information, see your dealer, call the ATV Safety Institute at 1-800-887-2887, or go to www.atvsafety.org. ©2026 Kawasaki Motors Corp., U.S.A.

TM/® & © 2026 TrueTimber Outdoors Holding Company, LLC. Manufactured and/or distributed under official license by Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit bolivia.kawasaki-la.com for full product details.